

Catálogo k-Uno



Fotos Código CAMARAS INFRAROJAS



TI-004

1/4" Sharp Color CCD 420TV Lines
PAL:510(H)*492(V) NTSC: 500(H)*582(V)
3.6/72°, 6/52° Blacklight Compensation: AUTO, S/R
Ratio:>48db,Gamma Correction:>0.45



TI-006

1/4" Sharp Color CCD 420TV Lines
PAL:510(H)*492(V) NTSC: 500(H)*582(V)
3.6/72°, 6/52° Angular field of View Blacklight Compensation:
AUTO, S/R Ratio:>48db,Gamma Correction:>0.45



TI-017

1/4" Sharp Color CCD 420TV Lines
PAL:510(H)*492(V) NTSC: 500(H)*582(V)
3.6/72°, 6/52° Angular field of View Blacklight Compensation:
AUTO, S/R Ratio:>48db,Gamma Correction:>0.45



TI-018

1/4" Sharp Color CCD 420TV Lines
PAL:510(H)*492(V) NTSC: 500(H)*582(V)
3.6/72°, 6/52° Angular field of View Blacklight Compensation:
AUTO, S/R Ratio:>48db,Gamma Correction:>0.45

YC-15P



YC-15K

**Color CCD/Waterproof Infrared /14 PCS 5mm IR
LEDs/ 12 meter IR distance /with Small Bracket**

YC-15H

CAMARAS BOX Y LENTES



TB-006

1/4" Sharp Color CCD 420TV Lines
PAL:510(H)*492(V) NTSC: 500(H)*582(V)
3.6/72°, 6/52° Angular field of View Blacklight Compensation:
AUTO, S/R Ratio:>48db,Gamma Correction:>0.45



TB-001

1/4" Sharp Color CCD 420TV Lines
PAL:510(H)*492(V) NTSC: 500(H)*582(V)
3.6/72°, 6/52° Angular field of View Blacklight Compensation:
AUTO, S/R Ratio:>48db,Gamma Correction:>0.45



TM-019

1/4" Color CCD 420TV Lines
PAL;720(H)*576(V),NTSC;720(H)*480(V)
3.6/72°, 6/52° Angular field of View Blacklight Compensation:
AUTO, S/R Ratio:>48db,Gamma Correction:>0.45



TY-003

1/4" Sony Color Super HAD 480TV Lines
PAL:510(H)*492(V);NTSC:500(H)*582(V)
3.6/72°, 6/52° Angular field of View Blacklight Compensation:
AUTO, S/R Ratio:>48db,Gamma Correction:>0.45



Manual
Iris

Focal Length:4mm
Mount:CS
Aperture:1.2
Angle of Views:76 degree



Manual
Zoom
Auto Iris

Focal Length:3.5mm--8mm
Mount:CS
Aperture:1.4
Angle of Views:20-140 degree
Match with TB-001/006

FOTO LENTE ZOOM

CAMARAS DOMO



TM-029

1/4" Color CCD 420TV Lines
12V/500mA-10~+50/+14~+122°C/□ Operation
Temperature;3.6/72°, 6/52° Angular field of View Blacklight
Compensation: AUTO, S/R Ratio:>48db,Gamma
Correction:>0.45



TD-015

1/4" Color CCD 420TV Lines
PAL;720(H)*576(V),NTSC;720(H)*480(V)
3.6/72°, 6/52°Angular field of View Blacklight Compensation:
AUTO, S/R Ratio: >48db,Gamma Correction:>0.45



DP-904P

Color CCD/1.0LUX/3.6mm lens/2.5 inch Dome

CAMARAS IP



H.264 Real time 0.5 lux audio WI-Fi

No incluye lentes



H.264 Real time 0.5 lux audio CMS

CAMARAS PTZ



HSP-660-K1 Economic high Speed Dome/ **Outdoor**/ With Wall Mount
Bracket and Power Adaptor



SAT-809 9 inch Indoor/Outdoor Spherical PTZ Decoder



SAT-807H 7 inch Indoor Dome PTZ Decoder



SAT-01 Outdoor PTZ Motor/AC24V



SAT-02 Indoor PTZ Motor/AC24V



SAT-03 Indoor Horizontal PTZ Motor/AC24V



SAD-01 Indoor/Outdoor PTZ Decoder



SAR-01 RS232 to 485 Converter

TARJETAS DVR



SDVR-404

4 channel video/Total 30FPS/MPEG-4/One PC support 4 cards/English Software/Windows 98/2000/NT

SDVR-404A



SDVR-604C

16 channel video/1 channel TV out/Total 120FPS/ENGINE-K/2 PCS DB Cable/One PC support 2 cards/English Software /Windows 98/2000/XP



GV-800

16 channel video/4 channel audio/Total 120 FPS/ MPEG-4/One PC support 1 card/Support Ver7.05 Software/V3 version /Windows 2000/XP/V3 version



iV-250

16 channel video/1 channel audio/Total 30FPS/ MPEG-4 /One PC support 1 card/ Support Ver7.05 Software /Windows 2000/XP/V3 version

DVR STANDALONE



Modelo TFTDVR -2004



SEDVR-104S

MJPEG/4 channel Video/Total 120 FPS display/ Total 30 FPS Recording/MJPEG/Motion detect/USB backup/ Remote Controller



SEDVR-316

H.264/Real-time D1 display /CIF recording/Network/VGA and AV output/SATA /Support 8 HDDs RAID/USB& CD-RW/DVD-RW Backup /Mouse Supported/ Email&FTP upload /CMS/Remote Controller



MJPEG/4 channel Audio Input/MJPEG/ Motion detect /USB backup/Remote controller/ Network Function /Support Removable HDD/ Support CD-RW Backup

ACCESORIOS



NT-601B

Passive Balun/1 channel Video/Color 400 Meters/B/W 600 Meters/Screw Connect / (A PAIR)



NT-602

Passive Balun/1 channel Video/Color 400 Meters/B/W 600 Meters/Mini Type/ (A PAIR)



NT-611

Passive Balun/1 channel Video/Color 400 Meters/B/W 600 Meters/No Cable



NT-611B

Passive Balun/1 channel Video/Color 400 Meters/B/W 600 Meters/With Cable



NT-2401T Active Balun/1 channel Video/Color 2400 Meters/B/W 3000 Meters (Transmitter)

NT-2401R Active Balun/1 channel Video/2400 Meters /B/W 3000 Meters(Receiver)



Bracket TZ-003

match with TI-006/017/018/TB-006



Bracket TZ-006

match with TB-001



SAL-10



SAL-15



SAL-30

Waterproof IR Illuminator



SAL-60



SAL-80



SAL-120

Waterproof IR Illuminator/8 mm High Power LED



SAL-160



SAP-02

**Switching Power Supply
100~240V AC**

**INPUT:
OUTPUT: 12V DC**



SAP-03



PA-04A

**Switching Power Supply/4 Channel output
OUTPUT:12V DC500 mA/Channel /total 2A**